


PROFIPRESS C-SERIES

Heavy duty gluing presses for all applications of gluing solid wood products




The ProfiPress C-Series DimterLine:


Heavy duty gluing presses for all applications of gluing solid wood products

The continuously working edge gluing plants by DimterLine are of great importance for an economic production of glued components and products. DimterLine offers plants in different sizes and classes for adapted solutions. It ranges from economic standard machines to special solutions of highest performance.


Applications and technical data




Thin wood products
With continuous ingoing boards, as cover layer of 3-sheet-panel, parquet, thick veneer



Panel products
Panels for furniture, large scale panels (house wall)



Special products
Inner layer of block boards and 3-sheet-panels. Boards are butt-jointed, collected in tracks and cut to panel length.



Japan Beams, window scantlings
JAS-certified Japan beams, scantlings


Timber length	300 mm – 6200 mm
Board width	20 mm – 150 mm
Board thickness	2.8 mm – 30 mm

Timber length	300 mm – 16200 mm
Board width	25 mm – 200 mm
Board thickness	9 mm – 60 mm

Timber length	300 mm – 6200 mm
Board width	25 mm – 150 mm
Board thickness	10 mm – 40 mm


Timber length	600 mm – 7200 mm
Board width*	60 mm – 160 mm
Board thickness	20 mm – 40 mm

*standing on edge



Intelligent heating technology

Shorter pressing period by radio frequency, hot water or thermo oil heating. Radio frequency with intelligent control for minimum cure time for completely cured and totally hardened joints. Thus, the space for throughfeed is extremely short = higher flexibility in production!



1 Precision glue application

Precision glue application for exact glue "beads". For durable gluing quality with low consumption of glue. For all applications of lateral gluing.



2 Feeding with down-holders

Optimum alignment of every single board by down-holders in front of infeed. Minimum mismatch provides little reworking. DIMTER patent: Return protection provides constant pressing power during throughfeed.



3 Automatic length cutting

Cutting of panel length during throughfeed. Saws are easily adjustable to requested panel length. Number of saws optional. Pieces are cut off and automatically removed.



4 Automatic width cutting

Automatic cutting to panel width. The required width is cut from the "endless" panel. Optimum yield: panel width is independent of board width!

PROFIPRESS C-SERIES



GRECON DIMTER Holzoptimierung Süd
GmbH & Co.KG
Rudolf-Diesel-Str. 14-16
89257 Illertissen
Germany

Phone +49 (0) 73 03 / 15-0
Fax +49 (0) 73 03 / 15-1 99
info@weinig.com
www.weinig.com